SAFETY DATA SHEET - SET

Pad N Pole[™] Sealant Type BRK Kit

Product ID numbers: BRK-250KIT1, BRK-250KITB6,

BRK-XXX (where XXX is the package code.)



Date Compiled: August 24, 2017

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

This product is a kit or a multi-part product with independent components. An SDS for each component is included. Do not separate SDSs.

Contains

BRK-A Pad N Pole Clear Part A SDS BRK-B Pad N Pole Clear Part B SDS HPWipe Cleaning Towelette

SDSs are classified according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Each Kit may or may not contain all SDS components

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: August 28, 2017 Revision Number: rev 10 supersedes 9

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: Polywater® Pad N Pole Repair Type BRK (Part A) 10865 (Clear Formula)

Product ID numbers: BRK-250KIT1, BRK-250KITB6,

BRK-XXX (where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Sealant/adhesive repair resin; Part A of two-part material

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Skin Sensitization, Cat 1; H317 Acute Toxicity, Cat 4, H332

Respiratory Sensitization, Cat 1; H334

Target Organ Toxicity (single exposure), Cat 3; H335

2.2 Label elements

Pictograms:

Contains: Hexamethylene diisocyanate oligomers, isocyanurate; Hexamethylene-di-isocyanate





Signal word: Danger

Hazard Statements:

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Precautionary Statements:

P261	Avoid breathing dust or vapors.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves, protective clothing and eye protection.
P284	In case of inadequate ventilation wear respiratory protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for
P304 + P340	breathing.
P342 + P311	If experiencing respiratory symptoms: Call a poison center or doctor.
P362 +P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local and national regulations.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

Component	CAS#	<u>Wt. %</u>	GHS Classification
Hexamethylene diisocyanate oligomers, isocyanurate	28182-81-2	≈100%	Skin Sens 1, Acute Tox 4, STOT SE 3
Hexamethylene-di-isocyanate	822-06-0	<0.5%	Acute Tox 4, Acute Tox 1, Skin Sens 1, Skin Irrit 2, Eye Irrit 2, Resp Sens1, STOT SE 3

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical

attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water. If

irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention.

Ingestion (Swallowing): If swallowed, rinse mouth and drink plenty of water. Do not induce vomiting. If

patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause allergic skin and respiratory reaction. Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

5.3 Advice for firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear full protective clothing, including appropriate respiratory protection.

6.2 Environmental precautions:

Prevent from entering waterways.

6.3 Methods materials for containment and cleaning up:

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash with a dilute ammonia solution.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Country/Source	Component	Long-term exposure limit 8 hr OEL, TWA	Short-term (ceiling) exposure limit – 15 min
USA – ACGIH TWA	Hexamethylene-di- isocyanate	0.005 ppm	
USA – NIOSH REL	Hexamethylene-di- isocyanate	0.005 ppm	0.02 ppm
Canada OEL (Manitoba, New Brunswick, Newfoundland, Northwest Territories, Nova Scotia, Nunavut)	Hexamethylene-di- isocyanate	0.005 ppm	
Canada (Québec)	Hexamethylene-di- isocyanate	0.005 ppm	
Canada (British Columbia)	Hexamethylene-di- isocyanate	0.005 ppm	0.01 ppm
Canada (Alberta)	Hexamethylene-di- isocyanate	Not established	

ACGIH, OSHA and NIOSH have not established any OELs for Hexamethylene diisocyanate oligomers, isocyanurate

8.2 Exposure controls

Respiratory protection:

Use with adequate ventilation to keep vapor concentration below acceptable limits. Observe OSHA standard 29 CFR 1910-94, 1910.107, 1910.108. Product dispensed through a static mixer and used as directed emits less than 0.001 ppm MDI vapor as tested by OSHA 47. Ventilation is not required for standard use. If product

Product Name: Polywater® Pad N Pole Repair Type BRK (Part A)

is use in a way that ventilation is not adequate, use approved chemical/mechanical filters designed to remove a combination of particulate and organic vapors in open and restricted areas. Use approved airline type respirators or hoods in confined areas. Observe OSHA standard 29 CFR 1910.134.

Revision Date: August 28, 2017

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Wear suitable protective clothing. Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance: Colorless to pale yellow

Odor threshold: None

pH: Does not apply

Freezing point: -20°C Boiling point: 150°C

Flash point: >320°F / >160°C (closed cup)

Evaporation rate: Not available **Flammability (solid, gas):** Does not apply

Upper/lower flammability or

explosive limits: Not available Vapor pressure: Not available Vapor density (Air = 1): 1.22 g/cm³ Specific gravity ($H_2O = 1$): 1.13 @ 25°C Solubility in water: Reacts

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not available

Viscosity: 600 mPas @ 25°C / 77°F

9.2 Other Information

Volatiles (Weight %): 0% VOC Content: 0 g/l

10. Stability and Reactivity

10.1 Reactivity:

Reacts with water, reacts with substances which contain active hydrogen.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid freezing, high temperatures, flame, high humidity and water contamination.

10.5 Incompatible materials:

Water, alcohols, amines, acids, alkalis, metal compounds.

10.6 Hazardous decomposition products:

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Allergic skin reaction symptoms include redness, swelling, blistering and itching.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes.

Inhalation (Breathing):

Material has low vapor pressure and inhalation hazard is expected to be minimal. Vapor exposure may cause irritation of the nose and throat. Symptoms may include burning sensation, coughing and shortness of breath, or other signs of respiratory distress. May cause allergic respiratory reaction below exposure guideline in susceptible individuals.

Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

Toxicity to Animals:

Hexamethylene diisocyanate oligomers, LD₅₀ (oral rat) >2500 mg/kg (OECD 423, female)

isocyanurate: LD₅₀ (dermal rabbit) >2000 mg/kg (OECD 402)

LD₅₀ (dermal rat) >2000 mg/kg (OECD 402) LC₅₀ (inhl rat) 0.39 mg/L (OECD 403, female)

Hexamethylene-di-isocyanate: LD₅₀ (oral rat) 746 mg/kg (OECD 401)

LD₅₀ (dermal rabbit) >7000 mg/kg (OECD 402) LC₅₀ (inhl rat) 0.124 mg/L (OECD Guideline 403)

Aspiration Hazard:

No aspiration hazard expected.

Chronic Exposure:

Reproductive Toxicity: Product is not considered hazardous to reproduction.

Mutagenicity: Product is not considered to be genotoxic.

Teratogenicity: Not available.

Specific Target Organ

Toxicity (STOT)Contains material which causes damage to the upper respiratory tract.

Toxicologically Synergistic

Products: Not available.

Carcinogenic Status: Not considered a carcinogen by IARC, NTP, ACGIH, OSHA, or the EPA.

Respiratory/Skin Sensitization

May cause sensitization by inhalation and skin contact..

12. Ecological Information

12.1 Toxicity:

Aquatic Toxicity:

Hexamethylene diisocyanate oligomers, EC₁₀ (72 hr): 370 mg/l Desmodemus subspicatus (algae) isocyanurate

Product Name: Polywater[®] Pad N Pole Repair Type BRK (Part A) Revision Date: August 28, 2017

Hexamethylene diisocyanate oligomers, EL₅₀ (48 hr): 127 mg/l Daphnia magna (invertebrate)

isocyanurate

Hexamethylene diisocyanate oligomers, ErC₅₀ (0-72 hr): >1000 mg/l Desmodemus subspicatus (algae)

isocyanurate

LC₅₀ (96 hr): >82.8 mg/l Brachydanio rerio (fish) Hexamethylene diisocyanate oligomers,

isocyanurate

Hexamethylene-di-isocyanate ErC₅₀ (0-72 hr): 77.4 mg/l Desmodemus subspicatus (algae)

Hexamethylene-di-isocyanate EC₅₀ (48 hr): 89.1 mg/l Daphnia magna (invertebrate) Hexamethylene-di-isocyanate LC₅₀ (96 hr): >82.8 mg/l Brachydanio rerio (fish)

Hexamethylene-di-isocyanate NOEC (72 hr): 11.7 mg/l Desmodemus subspicatus (algae)

12.2 Persistence and degradability: Not biodegradable

12.3 Bioaccumulation potential: Accumulation in organisms is not to be expected. 12.4 Mobility in soil: Adsorption to solid soil phase is not expected

12.5 Results of PBT and vPvB This product is not, nor does it contain a substance that is a PBT or

Assessment:

vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number: Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated ICAO/IATA-DGR: Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA Acute Chronic Fire Pressure Reactive Section 311/312 Reporting Yes Yes No Yes

CERCLA/SARA Sec 302 SARA Sec. 313 Components **Hazardous Substance RQ EHS TPQ** Toxic Release Yes (100 lbs) No No

Hexamethylene-di-isocyanate (822-06-0)

California Proposition 65:

This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm and may be subject to the requirements of California Proposition 65: None

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

NFPA Ratings: Health: 2

Fire: 1 Reactivity: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

Revision Date: August 28, 2017

Revision Number: 10 NA
Supersedes: May 3, 2017
Other: Not Applicable

Indication of Changes: Reviewed, slight format updates. New formulation, part numbers May 2017.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and

Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: May 3, 2017 Revision Number: 8 supersedes 7

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: Polywater® Pad N Pole Repair Type BRK (Part B) 84247 (Clear Formula)

Product ID numbers: BRK-250KIT1, BRK-250KITB6,

BRK-XXX (where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Sealant/adhesive repair resin; Part B of two-part material

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200.

This mixture is not hazardous under OSHA 29 CFR 1910.1200.

2.2 Label elements

Contains: None required.
Pictograms: None required.
Signal word: None required.
Hazard Statements: None required.
Precautionary Statements: None required.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	CAS#	<u>Wt. %</u>	GHS/CLP Classification
Polycarbonate diol mixture	Proprietary	60 - 100	Non-hazardous
Dibutyltin dilaurate	77-58-7	<0.1%	Acute Tox. 4, Skin Corr 1C, Skin Sens 1, Repr. 1B, Muta 2, STOT SE 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical

attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water. If

irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention.

Ingestion (Swallowing): If swallowed, get medical attention. Do not induce vomiting. If patient is

conscious, wash out mouth with water. Never give anything by mouth to an

unconscious person. Do not leave victim unattended.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Carbon monoxide, carbon dioxide, phosphorus oxides, silicon dioxide, hydrogen chloride gas.

5.3 Advice for firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear full protective clothing, including appropriate respiratory protection.

6.2 Environmental precautions:

Prevent from entering waterways.

6.3 Methods materials for containment and cleaning up:

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash with a dilute ammonia solution.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers dry, and away from excessive heat. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Country/Source	Component	Long-term exposure limit 8 hr OEL, TWA	Short-term (ceiling) exposure limit – 15 min
USA – ACGIH TWA	Dibutyltin dilaurate	0.1 mg/m ³	0.2 mg/m3
USA – OSHA Z1 PEL	Dibutyltin dilaurate	0.1 mg/m ³	
USA – OSHA Z1A TWA	Dibutyltin dilaurate	0.1 mg/m ³	
USA – NIOSH REL	Dibutyltin dilaurate	0.1 mg/m ³	
USA CA OEL	Dibutyltin dilaurate	0.1 mg/m ³	0.2 mg/m3
USA TN OEL	Dibutyltin dilaurate	0.1 mg/m ³	

8.2 Exposure controls

Respiratory protection:

Use with adequate ventilation to keep vapor concentration below acceptable limits.

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Clear liquid Appearance: Odor threshold: odorless pH: Not available Freezing point: Not available **Boiling point:** Not available Flash point: Not available **Evaporation rate:** Not available Flammability (solid, gas): Does not apply

Upper/lower flammability or

explosive limits: Not available Vapor pressure: Not available Vapor density (Air = 1): Not available Specific gravity ($H_2O = 1$): Not available Solubility in water: Not available

Partition coefficient: n-

octanol/water:

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not available

Not available

Not available

9.2 Other Information

Volatiles (Weight %): 0%
VOC Content: 0 g/l

10. Stability and Reactivity

10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid freezing, high temperatures, and moisture.

10.5 Incompatible materials :

Isocyanates, strong oxidizing agents and strong bases.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, phosphorus oxides, silicon dioxide, hydrogen chloride gas.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

May cause skin irritation

Irritation and Sensitization Potential:

May be a skin sensitizer.

Inhalation (Breathing):

May cause respiratory irritation.

Ingestion:

Low oral toxicity.

Toxicity to Animals:

Dibutyltin dilaurate LD₅₀ (oral rat) >2,000 mg/kg

LD₅₀ (dermal rabbit) > 2,000mg/kg

Aspiration Hazard:

No aspiration hazard expected.

Chronic Exposure:

Reproductive Toxicity: Not available.

Mutagenicity: Contains dibutyltin dilaurate, suspected of causing genetic defects.

Teratogenicity: Not available.

Specific Target Organ

Toxicity (STOT) Not available.

Toxicologically Synergistic

Products: Not available.

This mixture contains no listed carcinogens according to IARC, ACGIH, NTP

Carcinogenic Status: and/or OSHA in concentrations of 0.1% or greater.

12. Ecological Information

12.1 Aquatic Toxicity: No information available.
 12.2 Persistence and degradability: No information available.
 12.3 Bioaccumulation potential: No information available.
 12.4 Mobility in soil: No information available.

12.5 Results of PBT and vPvBThis product is not, nor does it contain a substance that is a PBT or

Assessment: vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number: Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated ICAO/IATA-DGR: Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	Reactive
Section 311/312 Reporting	No	No	No	No	No

CERCLA/SARA Sec 302 SARA Sec. 313
dous Substance RQ EHS TPQ Toxic Release

<u>Components</u> <u>Hazardous Substance RQ</u> <u>EHS TPQ</u> <u>Toxic Releas</u>

The components of Foam Sealant FST - Part B are not affected by these Superfund regulations.

NFPA Ratings: Health: 1
Fire: 1
Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Hazard Statements: None

Revision Date: May 3, 2017

Revision Number:

Other:

Supersedes: February 8, 2017 Not Applicable

Indication of Changes: Written in accordance with the provisions of OSHA 1910.1200 App D (GHS format)

New formulation, new name and part numbers.

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: July 31, 2017 Revision Number: 5, supersedes 4

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: Type HP™ Cleaner/Degreaser Saturated Towel/Wipe Package

Product ID numbers: HP-1, HP-1B, HP-1M,

HP-P158ID, HP-P158IDB, HP-P158IDM, HP-3P158IDS, HP-6P158ID,

HP-P1K, HP-P63 HP-D72, HP-D72E, HP-P31212, HP-P369,

HP-T369/S, HP-T369/SH, HP-T369/SH48, HP-T369/S-D

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses:Electrical cleaningList of advices against:Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Skin Sens 1 H317 Flam Lig 4 H227

2.2 Label elements

Contains: Petroleum distallates, hydrotreated light; d-Limonene



Pictograms:

Signal word: Warning

Hazard Statements:

H227 Combustible liquid

H317 May cause an allergic skin reaction.

Precautionary Statements:

P210 Keep away from flames and hot surfaces. No smoking.
P261 Avoid breathing fumes.
P280 Wear protective gloves.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical advice.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local and national regulations.

Notes: Aspiration classification not applied due to the physical form of the product.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	CAS#	<u>EC #</u>	<u>Wt. %</u>	GHS/CLP Classification Asp. Tox. 1 H304; EUH066
Petroleum distillates, hydrotreated light	64742-47-8	265-149-8	< 100	Skin Irrit. 3 H316; Flam Liq 4 H227
d-Limonene	5989-27-5	227-813-5	< 10	Flam Liq 3, H226 Skin Irrit 2, H315 Skin Sens 1, H317 Aquatic Chronic 1, H410 Aquatic Acute 1, H400

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth. If victim is drowsy or

unconscious, place on the left side with head down. Do not leave victim

unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates CO, CO2 and smoke. Smoke may be acrid and fumes irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Petroleum Distillates, hydrotreated light (64742-47-8)

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
Manufacturer, RCP* TWA	1200 mg/m ³	
USA, ACGIH TWA	Not established	Not established
USA, OSHA PEL	2000 mg/m ³ , 500 ppm (as petroleum distillates (naphtha))	
British Columbia	200 mg/m ³	
Alberta, Quebec, Yukon, Saskatchewan, Ontario*	Not established	

D-Limonene (5989-27-5)

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA ACGIH TWA	Not established	Not established
USA OSHA PEL Alberta, Quebec, Yukon, British Columbia,	Not established	Not established
Saskatchewan, Ontario*	Not established	Not established

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. Towelette limits solvent vapor exposure. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material. Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

Eye protection:

None necessary. Wipe package eliminates splash hazard. Do not allow wipe/towel to directly contact eyes.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties (bulk liquid)

Appearance: Clear, colorless liquid with a very light citrus scent.

Odor threshold:

pH:

Does not apply

Freezing point:

Solve in the state of the st

Flash point: >140°F (>60.5°C), Closed Cup (PMCC)

Evaporation rate: <0.1 (n-butyl acetate = 1) **Flammability (solid, gas):** Not applicable to liquids

Upper/lower flammability or

explosive limits: LEL = 0.7% UEL = 6.1%-7.0% Vapor pressure: <1 mm Hg < 134 Pa @ 20°C

Vapor density (Air = 1): > 1.0Specific gravity (H₂O = 1): 0.79 Solubility in water: Nil

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100% VOC Content: 790 g/l

10. Stability and Reactivity

^{*} reciprocal calculation procedure for total hydrocarbons

^{**} Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eve contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It may cause an allergic skin reaction.

Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Petroleum distillates,

hydrotreated light: LD₅₀ (oral rat) >5000 mg/kg

 LD_{50} (dermal rabbit) >2000 mg/kg LC_{50} (inhl rat) >4.3mg/L, 4 hours

d-Limonene: LD₅₀ (oral rat) >5000 mg/kg

LD₅₀ (dermal rabbit) 5000 mg/kg

RD₅₀ 1000 ppm

Aspiration hazard

Liquid solvent has an aspiration hazard. This route of exposure is not expected for towelette form.

Chronic Exposure:

Reproductive Toxicity:Not available.Mutagenicity:Not available.Teratogenicity:Not available.

Specific Target Organ

Toxicity (STOT) No end point data.

Toxicologically Synergistic

Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Ecotoxicity: No information available.

Aquatic Toxicity: No information available.

12.2 Persistence and degradability: Expected to be biodegradable.

12.3 Bioaccumulation potential: 12.4 Mobility in soil:No information available.

12.5 Results of PBT and vPvBThis product is not, nor does it contain a substance that is a PBT or

Assessment: vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number: Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated ICAO/IATA-DGR: Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

Components

All components are listed on the TSCA inventory.

CERCLA/SARA Sec 302 SARA Sec. 313
Hazardous Substance RQ EHS TPQ Toxic Release

Components are not affected by these Superfund regulations.

NFPA Ratings: Health: 1

Fire: 2 Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Mixture classification according to Regulation (EC) No 1272/2008: Classification Procedure

H227 Combustible liquid

H317 May cause an allergic skin reaction.

Classification Frocedure

Physical Testing Calculation method.

Revision Date: July 31, 2017

Revision Number: 5 NA

Supersedes: January 2, 2015 **Other:** Not Applicable

Indication of Changes: Sections 1.1, 2, 8.1 updated: additional product codes, additional precautionary

statements, and additional information on exposure limits.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and

Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.