Revision Date: September 15, 2017 Revision Number: 8 supersedes 7

# **SAFETY DATA SHEET**

# 1. Identification of the substance/mixture and of the company

#### 1.1 Product identifier

Product Name: Type FD<sup>™</sup> Electrical Contact Cleaner Aerosol

Product ID numbers: FD-9, FD-9M

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Electrical Cleaner/Degreaser

**List of advices against:** Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

#### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

#### 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Aerosol 1 H222, H229
Skin Irrit. 2 H315
STOT SE 3 H336
Rep. Tox. 2 H361

# 2.2 Label elements

This product is intended for consumer use and is labeled according to CPSC guidelines and not to GHS guidelines listed below. It is safe for consumers and other users under normal and reasonably foreseeable use. The SDS contains valuable information for industrial workplace conditions.

Contains: Isohexanes, Ethanol, n-Pentane, n-Hexane, Isopropanol, Carbon Dioxide







Pictograms:

Signal word: Danger

**Hazard Statements:** 

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness

H361 Suspected of damaging fertility or the unborn child

### **Precautionary Statements:**

**Product Name:** Type FD™ Electrical Contact Cleaner Aerosol **Revision Date:** September 15, 2017

	P210	Keep away from sparks, flames and hot surfaces. No smoking.			
	P211	Do not spray on an open flame or other ignition source.			
	P251	Do not pierce or burn, even after use.			
	P280	Wear protective gloves.			
	P261	Avoid breathing vapor.			
	P271	Use only outdoors or in a well-ventilated area.			
	P280	Wear protective gloves and eye protection.			
	P303 + P361 + P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water			
	P332 + P313	If skin irritation occurs: Get medical attention.			
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
	P308 + P313	If exposed or concerned: Get medical advice.			
	P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.			
	P501	Dispose of contents/container in accordance with local and national regulations.			
Notes:		Aspiration classification not applied due to the physical form of the product.			

**2.3 Other hazards:** No information available.

### 3. Composition/Information on Ingredients

<u>Component</u>	CAS#	EC #	Wt. %	<b>GHS/CLP Classification</b>
Isohexanes	107-83-5	203-523-4	80 -95%	Flam Liq 2, H225;
				Asp Tox 1, H304;
				Skin Irrit 2, H315
				STOT SE 3, H336
Ethanol	64-17-5	200-578-6	<15%	Flam Liq 2, H225;
n-Pentane	109-66-0	203-692-4	<3%	
n-Hexane	110-54-3	203-777-6	<3%	Flam Liq 2, H225;
				Asp Tox 1, H304;
				Skin Irrit 2, H315
				STOT SE 3, H336;
				Rep Tox 2, H 361f
Isopropanol	67-63-0	200-661-7	<2%	Flam Liq 2, H225;
				Eye Irrit. 2, H319;
				STOT SE 3, H336
Carbon Dioxide	124-38-9	204-6969-9	<8%	

#### 4. First Aid Measures

#### 4.1 Description of first aid measures

**Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth unless directed to do so by

medical personnel. Get medical attention if symptoms appear.

### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

r.

**Product Name:** Type FD™ Electrical Contact Cleaner Aerosol

Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. This route not expected in aerosol package.

Revision Date: September 15, 2017

### 5. Firefighting Measures

### 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

### 5.2 Special hazards arising from the substance or mixture

Flammable aerosol product. Vapors may travel considerable distance to source of ignition and flash back. May burn with nearly invisible flame.

### Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

# 5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers. Aerosol cans can build up pressure and explode when exposed to temperatures greater than 120°F (49°C).

### 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

#### 6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

### 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

# 7. Handling and Storage

# 7.1 Precautions for safe handling

Extremely flammable aerosol. Keep containers cool, dry, and away from sources of ignition. Do not expose container to direct sunlight or temperatures above 50°C/122°F. Do not transport or store near heat sources. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

# 7.2 Conditions for safe storage, including incompatibilities

Do not transport or store near heat sources. Keep cans dry and away from sources of ignition. Do not puncture or incinerate container. Store this product with adequate ventilation.

### 7.3 Specific end uses

See technical data sheet on this product for further information.

#### 8. Exposure Controls / Personal Protection

#### 8.1 Control parameters

**Exposure limits and recommendations:** 

Isohexane (107-83-5)

Country/Source

Long-term exposure limit -Short-term exposure limit -8 hr TWA 15 min

Revision Date: September 15, 2017

USA, ACGIH 500 ppm 1000 ppm

100 ppm, 350 mg/m<sup>3</sup> USA, NIOSH TWA 510 ppm, 1800 mg/m<sup>3</sup> Alberta 1760 mg/m<sup>3</sup>, 500 ppm 3500 mg/m<sup>3</sup>, 1000 ppm 1760 mg/m<sup>3</sup>, 500 ppm 3500 mg/m<sup>3</sup>, 1000 ppm Quebec

Saskatchewan\* 500 ppm 1000 ppm

Ethanol (64-17-5)

Long-term exposure limit -Short-term exposure limit -Country/Source 8 hr TWA 15 min

USA, OSHA NIOSH 1900 mg/m<sup>3</sup>, 1000 ppm 1881 mg/m<sup>3</sup>, 1000 ppm USA, ACGIH Alberta 1880 mg/m<sup>3</sup>, 1000 ppm

Ontario 1000 ppm

1880 mg/m<sup>3</sup>, 1000 ppm Quebec

Saskatchewan\* 1000 ppm 1250 ppm

n-Pentane (109-66-0)

Long-term exposure limit -Short-term exposure limit -8 hr TWA 15 min

Country/Source

USA, OSHA NIOSH 1000 ppm British Columbia

Alberta 600 ppm, 1700 mg/m<sup>3</sup> Ontario 600 ppm Quebec 120 ppm, 350 mg/m<sup>3</sup>

Saskatchewan 600 ppm 750 ppm

n-Hexane (110-54-3)

Long-term exposure limit -Short-term exposure limit -Country/Source 8 hr TWA 15 min

USA, OSHA, NIOSH 180 mg/m<sup>3</sup>, 50 ppm

USA, ACGIH 50 ppm

British Columbia 200 ppm 400 ppm

Alberta 176 mg/m<sup>3</sup>, 50 ppm Ontario (skin) 50 ppm 176 mg/m<sup>3</sup>, 50 ppm Quebec

Saskatchewan (skin) 50 ppm 62.5 ppm

Isopropanol, 2-propanol (67-63-0)

Long-term exposure limit -Short-term exposure limit -Country/Source 8 hr TWA 15 min

USA, OSHA NIOSH 980 mg/m<sup>3</sup>, 400 ppm 1,225 mg/m<sup>3</sup>, 500 ppm

USA, ACGIH 200 ppm 400 ppm British Columbia 400 ppm 200 ppm

Alberta 492 mg/m<sup>3</sup>, 200 ppm 984 mg/m<sup>3</sup>, 400 ppm

Ontario 200 ppm 400 ppm

Quebec 985 mg/m<sup>3</sup>, 400 ppm 1,230 mg/m<sup>3</sup>, 500 ppm

Saskatchewan\* 400 ppm 200 ppm

**Product Name:** Type FD™ Electrical Contact Cleaner Aerosol

\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

Revision Date: September 15, 2017

#### 8.2 Exposure controls

### Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

### Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

## Eye protection:

Safety glasses recommended.

# Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

### 9. Physical and Chemical

### 9.1 Information of basic physical and chemical properties (bulk liquid)

**Appearance:** Clear, colorless liquid; mild odor.

Odor threshold:Not availablepH:Does not applyFreezing point:Not availableBoiling point:144°F / 62°CFlash point:>0°F / -18°C (TCC)

**Evaporation rate:** 1.7 (n-butyl acetate = 1) **Flammability (solid, gas):** Not applicable to liquids

Flammability limits: LEL: 1.2% Vapor pressure: Not available Vapor density (Air = 1): >1(Air = 1) Specific gravity ( $H_2O = 1$ ): 0.67

Solubility in water: Not available

Coefficient of Water/Oil

Distribution:Not availableAuto-ignition temperature:750.2°F / 399°CDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100% VOC Content: 670 g/l

### 10. Stability and Reactivity

#### 10.1 Reactivity:

See remaining headings in Section 10.

# 10.2 Chemical stability:

Stable

### 10.3 Possibility of hazardous reactions:

None known.

#### 10.4 Conditions to avoid:

**Product Name:** Type FD™ Electrical Contact Cleaner Aerosol **Revision Date:** September 15, 2017

Avoid heat, flame, and sparks.

### 10.5 Incompatible materials:

Strong oxidizing agents.

### 10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

#### 11.1 Information on toxicological effects:

### **Acute toxicity**

# Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

#### Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

#### Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

#### Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

# Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

#### **Toxicity to Animals:**

Ethanol LD<sub>50</sub> (oral rat) 9000 mg/kg

Draize test, rabbit eye 500 mg/24 hours Mild

LC<sub>50</sub> (inhl rat) 20000, 10 hours

n-Pentane LC<sub>50</sub> (inhl rat) 364000 mg/m<sup>3</sup>, 4 hours

n-Hexane LD<sub>50</sub> (oral rat) 25000 mg/kg

LC<sub>50</sub> (inhl rat) 48000, 4 hours

Isopropanol LD<sub>50</sub> (oral rat) 5000 mg/kg

 $LD_{50}$  (dermal rabbit) 12800 mg/kg  $LC_{50}$  (inhl rat) 12000, 8 hours

**Chronic Exposure:** 

Reproductive Toxicity:No data available.Mutagenicity:No data availableTeratogenicity:No data available

Specific Target Organ

**Toxicity (STOT)** No end point data.

**Toxicologically Synergistic** 

**Products:** Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components. ACGIH classifies a component, n-hexane as Class A4, not classifiable for human or

animal and IARC classifies it as Class 3. not classifiable for human.

## 12. Ecological Information

#### 12.1 Toxicity:

**Ecotoxicity:** No information available.

Aquatic Toxicity: Toxic to aquatic organisms, may cause long-term adverse

Page **6** of **8** 

Product Name: Type FD™ Electrical Contact Cleaner Aerosol Revision Date: September 15, 2017

effects in the aquatic environment.

**n-Hexane** 96 h LC<sub>50</sub> Fathead Minnow (fish) 2.5 mg/l

48 h EC<sub>50</sub> Daphnia magna (water flea) 3,878 mg/l

3 h EC<sub>50</sub> Fresh water algae 12,840 mg/l

Isopropanol 96 h LC<sub>50</sub> Fathead Minnow (fish)> 1000 μl/l

48 h LC<sub>50</sub> Golden Orfe 8970 - 9280 mg/l 96 h LC<sub>50</sub> Daphnid (crustacean)> 1000  $\mu$ l/l

12.2 Persistence and degradability:No information available12.3 Bioaccumulation potential:No information available12.4 Mobility in soil:No information available

12.5 Results of PBT and vPvB This product is not, nor does it contain a substance that is a

Assessment: PBT or vPvB.

12.6 Other adverse effects: None known.

#### 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

# 14. Transport Information

UN Number: 1950

**UN Proper shipping name:** AEROSOLS, Flammable, less than 1 liter each, Class 2.1, LTD QTY

Transport hazard class(es): Class 9

Packing group:

Environmental hazards:

Special precautions:

Not Applicable

None known

None known

Not Regulated

ICAO/IATA-DGR: Consumer Commodity, ID 8000, Class 9, LTD QTY

IMDG: UN 1950, AEROSOLS, Flammable, less than 1 liter each, Class 2.1, LTD

QTY

# 15. Regulatory Information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARAAcuteChronicFirePressureReactiveSection 311/312 ReportingYesNoYesNoNo

CERCLA/SARA Sec 302 SARA Sec. 313

Hazardous Substance RQ
Yes (5000 lbs) Ro Toxic Release
Yes (1%)

NFPA Ratings: Health: 1

Fire: 3 Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

### **European Union**

Components

n-Hexane

**Product Name:** Type FD™ Electrical Contact Cleaner Aerosol

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Revision Date: September 15, 2017

#### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

#### **Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

# 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

#### 16. Other Information

### Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Revision Date:** September 15, 2017

Revision Number: 8

**Supersedes:** December 18, 2015 **Other:** Not Applicable

Indication of Changes: Updated sections 2, 8, 16; updated hazard and precaution statements, additional

exposure data, general formatting.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and

Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.