STAINLESS STEEL LASHING WIRE

- Available in 430, 302, 304 and 316 stainless steel alloy
- Packaged as coils with 6 coils per carton



Alloy	Dia (mm)	Coil OD(cm)
430	0.045" (1.1)	5.38" (13.7)
430	0.065" (1.6)	6.50" (16.5)
430	0.065" (1.6)	5.50" (14.0)
302	0.045" (1.1)	5.38" (13.7)
316	0.045" (1.1)	5.38" (13.7)
302	0.038" (1.0)	5.38" (13.7)
316	0.061" (1.5)	5.50" (14.0)
316	0.065" (1.6)	5.50" (14.0)
304	0.045" (1.1)	5.38" (13.7)
	430 430 430 302 316 302 316 316	430 0.045" (1.1) 430 0.065" (1.6) 430 0.065" (1.6) 302 0.045" (1.1) 316 0.045" (1.1) 302 0.038" (1.0) 316 0.061" (1.5) 316 0.065" (1.6)

P/N	Coil Length (m)	Coil Width (cm)	Weight (kgs)	Note
71530	1200' (366)	1.81" (4.6)	6.5 lbs. (2.9)	1
71531	650' (198)	1.69" (4.3)	7.5 lbs. (3.4)	3
71532	450' (137)	1.69" (4.3)	5.3 lbs. (2.4)	2
71533	1200' (366)	1.81" (4.6)	6.5 lbs. (2.9)	1
71534	1200' (366)	1.81" (4.6)	6.5 lbs. (2.9)	1
71535	1600' (488)	1.81" (4.6)	6.5 lbs. (2.9)	1
71540	650' (198)	1.81" (4.6)	7.0 lbs. (3.2)	2
71541	450' (137)	1.69" (4.3)	5.3 lbs. (2.4)	2
71542	1200' (366)	1.81" (4.6)	6.5 lbs. (2.9)	1

NOTES:

- 1 Fits Standard C2, J2, Apollo & Sierra Lasher. Fits Modified G Lasher.
- 2 Fits Standard G Lasher. Fits Modified C2, J2 & Apollo Lasher.
- 3 Fits B Lasher Only (No Longer Manufactured).